

Indoor Model		MCFT-60CB(R410A)	
Outdoor Model		MCFT-60CB(R410A)	
Power supply		V-ph-Hz	220~230-1-60
Cooling	Capacity	Btu/h	60000
	Input	W	5920
	EER	W/W	2.97
Heating	Capacity	Btu/h	/
	Input	W	/
	COP	W/W	/
Indoor fan motor	Model		YKSS-130-4-1L
	Old Model		
	Qty		2
	Input	W	216/186/171/162
	Capacitor	uF	6.5UF/450V
	Speed(Hi/Med/Lo)	r/min	1640/1530/1430/1370
Indoor coil	Number of rows		4
	Tube pitch(a)x row pitch(b)	mm	21x13.37
	Fin spacing	mm	1.3
	Fin type		Hydrophilic aluminium
	Tube outside dia.and type	mm	Φ7 innergroove tube
	Coil length x height x width	mm	1375x546x53.48
	Number of circuits		12
Indoor air flow(Hi/Med/Lo)		m ³ /h	2890/2422/2281
Indoor noise level (sound pressure)(Hi/Med/Lo)		dB(A)	58.3/56.7/55.7
Throttle type			Throttle valve
Indoor unit	Dimension (WxDxH)	mm	1650x675x235
	Packing (WxDxH)	mm	1725x755x313
	Net/Gross weight	kg	45.5/51.5
Design pressure		MPa	4.2/1.5
Drainage water pipe diameter		mm	ODΦ25
Refrigerant piping	Liquid side/Gas side	mm(inch)	Φ9.52/Φ22(3/8"/7/8")
Controller			Remote control
Operation temperature		°C	17~30
Room temperature	Cooling	°C	17~32
	Heating	°C	/
Qty'per 20' /40' /40'HQ (indoor unit)			72/147/167