

			MAS36H2AMV-X
Product Code			22022016016340
Power supply	Voltage type		208/230V,1Ph
	Supply frequency		60Hz
Max.Input consumption	Max.Input consumption	W	4800
Max.Current	Max.Current	A	21
Min. Circuit ampacity	Min. Circuit ampacity	A	25
Max.Fuse	Max.Fuse	A	35
Compressor	Model		KTF250D22UMT
	Type		ROTARY
	Brand		GMCC
	Capacity	W	8095
	Input	W	2200
	Rated current	A	10
	Rated current(Certification)	A	18
	LRA (Locked rotor amp)	A	/
	Thermal protector		/
	Thermal protector position		NA
	Refrigerant oil/oil charge	mL	VG74/670
Outdoor Fan motor	Model		ZKFN-120-8-2
	Input	W	150.0
	RLA (Certification)	A	0.5
	Speed(High/Mi/Low)	r/min	1150/1050/900/850
	Capacitor	μF	/
	Capacitor class		/
Condenser	Insulation class		B
	Number of rows		3
	Tube outside dia	mm	φ7
	Tube outside type		Inner groove tube
	Tube pitch(a)x row pitch(b)	mm	21x13.37
	Fin spacing	mm	1.4
	Fin type (code)		Hydrophilic aluminum
	Coil length x height x width	mm	1000x756x13.37+980x756x13.37+965x756x13.37
	Number of circuits		6
Outdoor side air flow(Hi)	Outdoor side air flow(Hi)	m3/h	3800
Dimension(W*D*H)	Body_Width(W)	mm	946
	Body_Depth(D)	mm	410
	Body_Height(H)	mm	810
Packing(W*D*H)	Packing_Width(W)	mm	1090
	Packing_Depth(D)	mm	500
	Packing_Height(H)	mm	885
Net/Gross weight	Net weight	Kg	68.1
	Gross weight	Kg	72.1
Refrigerant	Refrigerant type		R410A
	Refrigerant charge		119.9
	Refrigerant charge unit		ozs
	GWP(EU)		1430
	CO2 Quantity(EU)		0
	Additional refrigerant per metre	g/m	30
Throttle type	Throttle type		电子膨胀阀+毛细管(EXV+Capillary)
India specification	India rotor diameter	mm	0
Loading quantity 20'GP/40'GP/40'HQ	Loading quantity_20'GP	set	44
	Loading quantity_40'GP	set	96
	Loading quantity_40'HQ	set	138