

			MAW05C1OUM	MAW08C1OUM	MAW12C1OUM
Power supply		Ph-V-Hz	115V,1Ph,60Hz	115V,1Ph,60Hz	115V,1Ph,60Hz
Cooling	Current (按铭牌)	A	4.60	6.75	9.5
	EER	W/W (Btu/h/W)	3.253	/	/
Capacity			5000	8000	12000
Rated input consumption		W	580	1050	1354
Rated current		A	5.5	10.3	12.79
Starting current		A	17	30.3	38.37
Compressor	Model		KSK44E11VAJA	KSN66E11VBZC1	KSM103E12VEZF
	Type		ROTARY	ROTARY	/
	Brand		GMCC	GMCC	GMCC
	Capacity	W	1530	2395	/
	Input	W	392	577	/
	Rated current	A	3.5	5.10	/
	Locked rotor Amp(LRA)	A	19	36	/
	Thermal protector		内置	/	/
	Thermal protector position		NA	NA	/
	Capacitor	uF	35.0	50.0	/
Refrigerant oil/oil charge	ml	140	190	/	
Fan motor	Model		YKTS-35-4-60L	YKTS-60-4-56L	YKTS-90-4-12L
	Input	W	56.0	95.0	145.0
	Rated current	A	0.514	0.91	1.25
	Capacitor	uF	6	15	15
	Speed(hi/mi/lo)	r/min	1540/1350/1210	1540/1340/1200	1585/1365/1246
	Capacitor class		P2	S2	P2
	Insulation class		B	B	B
	Waterproofing class		/	/	/
Evaporator	a.Number of rows		2	3	3
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37	21x13.37	21x13.37
	c.Fin spacing	mm	1.2	1.2	1.2
	d.Fin type (code)		Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum
	e.Tube outside dia.and type	mm	Φ7,Inner groove tube	Φ7,Inner groove tube	Φ7,Inner groove tube
	f.Coil length x height x width	mm	275x210x26.74	320x210x40.11	325x252x40.11
	g.Number of circuits		1	2	2
Indoor side air flow(Hi/Mi/Lo)	m3/h	253/232/218	320/280//	513////	
Indoor side noise level (Hi/Mi/Lo)	dB(A)	56/54/52	////	////	
Condenser	a.Number of rows		2	2	3
	b.Tube pitch(a)x row pitch(b)	mm	19.5x11.6	19.5x11.6	19.5x11.6
	c.Fin spacing	mm	1.2	1.2	1.2
	d.Fin type (code)		Inner groove tube	Inner groove tube	Inner groove tube
	e.Tube outside dia.and type	mm	Φ5,Inner groove tube	Φ5,Inner groove tube	Φ5,Inner groove tube
	f.Coil length x height x width	mm	350x293x23.2	409x331.5x23.2	415x351x34.8
	g.Number of circuits		1	1	2
Outdoor side noise level(Hi)	dB(A)	60	/	/	
Refrigerant type	kg	R32	R32	R32	
Design pressure	Mpa	///	///	///	
Plug type		LCDI(5-15P)	LCDI(5-15P)	LCDI(5-15P)	
Control type		遥控式(Remote Control)	遥控式(Remote Control)	遥控式(Remote Control)	
Operation temp	indoor(cooling/heating)	°C	17-32//	///	///
	outdoor(cooling/heating)	°C	18-43//	///	///
Application area (Cooling Standard)	m ²	7-10	11-16	16-23	
Dimension(W*D*H)	mm	406x335x306	471x400x340	545x482x372	
Packing (W*D*H)	mm	455x390x380	560x455x380	586x557x430	
Net/Gross weight	Kg	16/18	20.59/23.32	28.9/31.9	
Loading quantity 20' /40' /40'HQ	Pieces	468/918/1050	318/642/745	190/410/498	