Indoor			PISO TECHO	CASSETTE	FAN&COIL	PISO TECHO	CASSETTE	FAN&COIL	PISO TECHO	CASSETTE	FAN&COIL	PISO TECHO	CASSETTE	FAN&COIL	PISO TECHO	CASSETTE	FAN&COIL	PISO TECHO	CASSETTE	FAN&COIL	PISO TECHO	CASSETTE	FAN&COIL	PISO TECHO	CASSETTE	FAN&COIL
Market Model			MFM-F182C/DLN1	MFM-F182C/Q4N1	MFM-F182C/T2N1	MFM-F242C/DLN1	MFM-F242C/Q4N1	MFM-F242C/T2N1	MFM-F362C/DLN1	MFM-F362C/Q4N1	MFM-F362C/T2N1	MFM-F363C/DLN1	MFM-F363C/Q4N1	MFM-F363C/T2N1	MFM-F482C/DLN1	MFM-F482C/Q4N1	MFM-F482C/T2N1	MFM-F483C/DLN1	MFM-F483C/Q4N1	MFM-F483C/T2N1	MFM-F602C/DLN1	MFM-F602C/Q4N1	MFM-F602C/T2N1	MFM-F603C/DLN1	MFM-F603C/Q4N1	MFM-F603C/T2N1
Power supply	Voltage type	/	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220V,1Ph	220-230V,1Ph	220-230V,1Ph	220V,1Ph	220-230V,1Ph
	Supply frequency	/	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz
Fan motor	Model	/	YKSS-55-4-9-3	YKT-42-6-6	YKSS-74-4-16-1	YKSS-115-4-1-2	YKS-125-6-6	YKSS-115-4-21	YKSS-85-4-1L-2	YKS-125-6-6	YKSS-115-4-21	YKSS-85-4-1L-2	YKS-125-6-6	YKSS-115-4-21	YKSS-85-4-1L-2	YKS-125-6-6	YKSS-480-4-2	YKSS-85-4-1L-2	YKS-125-6-6	YKSS-480-4-2	YKSS-130-4-1L	YKS-125-6-6	YKSS-480-4-2	YKSS-130-4-1L	YKS-125-6-6	YKSS-480-4-2
	Input	W	175.0	81.0	163.0	236.0	242.0	253.0	166.0	242.0	253.0	166.0	242.0	253.0	166.0	242.0	/	166.0	242.0	/	216.0	242.0	/	216.0	242.0	/
	RLA (Rated current)	A	0.77	0.46	0.9	1.03	1.05	1.095	0.72	1.05	1.095	0.72	1.05	1.095	0.72	1.05	2.75	0.72	1.05	2.75	0.94	1.05	2.75	0.94	1.05	2.75
	LRA (Locked rotor amp)	A	/	/	1.08	/	/	1.53	/	/	1.53	/	/	1.53	/	/	5.38	/	/	5.38	/	1.3	5.38	/	1.3	5.38
	Speed(Hi/Mi/Lo)	r/min	1250/980/810	650/580/510/430	920/760/640/570	1263/1123/1000	780/715/600/550	1050/900/750/650	1435/1295/1165	780/600/550	1050/900/750/650	1435/1295/1165	780/600/550	1050/900/750/650	1435/1295/1165	780/715/600/550	1040/900/800	1435/1295/1165	780/715/600/550	1040/900/800	1640/1530/1430/1370	780/715/600/550	1000/900/800	1640/1530/1430/1370	780/715/600/550	1000/900/800
	Capacitor	μF	2.5	2.5	3.5	5	3.5	5	2.5	4.5	8	2.5	4.5	8	2.5	4.5	20UF/450V	2.5	4.5	20UF/450V	6.5	4.5	20	6.5	4.5	20
	Capacitor class	/	P2	P2	P2	P2	P0	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2
	Winding resistance	Ω	/	/	66	/	/	27.5	/	/	27.5	/	/	27.5	/	/	9.5	/	/	9.5	/	49	9.5	/	49	9.5
	Insulation class	/	E	B	B	B	B	F	B	B	F	B	B	F	B	B	F	B	B	F	B	B	F	B	B	F
	Waterproofing class	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/	IPX0	/	/	IPX0	/	/	IPX0	/	/	IPX0
Evaporator	Number of rows	/	3.0	2.0	4.0	2.0	2.0	3.0	3.0	3.0	4	3.0	3.0	4	3.0	3.0	4	3.0	3.0	4	4.0	3	4	4.0	3	4
	Tube outside dia	mm	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7
	Tube outside type	/	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube
	Tube pitch(a)x row pitch(b)	mm	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37
	Fin spacing	mm	1.3	1.4	1.4	1.3	1.4	1.4	1.3	1.4	1.4	1.3	1.4	1.4	1.3	1.4	1.5	1.3	1.4	1.5	1.3	1.4	1.5	1.3	1.4	1.5
	Fin type (code)	/	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum
	Coil length x height x width	mm	795x294x40.11	2010x168x26.74	695x252x53.48	935x294x26.74	2010x210x26.74	915x294x40.11	1300x294x40.11	2080x252x40.11	915x294x53.48	1300x294x40.11	2080x252x40.11	915x294x53.48	1300x294x40.11	2080x252x40.11	1030x378x53.48	1300x294x40.11	2080x252x40.11	1030x378x53.48	1375x294x53.48	2080x252x40.11	1030x378x53.48	1375x294x53.48	2080x252x40.11	1030x378x53.48
	Number of circuits	/	7	8	6	6	10	7	10	12	7	10	12	7	10	12	8	10	12	8	12	12	8	12	12	8
Dimension(W*D*H)	Body_Length(W)	mm	1068	840	880	1285	840	1100	1650	840	1100	1650	840	1100	1650	840	1200	1650	840	1200	1650	840	1200	1650	840	1200
		inch	42.05	33.07	34.65	50.59	33.07	43.31	64.96	33.07	43.31	64.96	33.07	43.31	64.96	33.07	47.24	64.96	33.07	47.24	64.96	33.07	47.24	64.96	33.07	47.24
	Body_Width(D)	mm	675	840	674	675	840	774	675	840	774	675	840	774	675	840	874	675	840	874	675	840	874	675	840	874
		inch	26.57	33.07	26.54	26.57	33.07	30.47	26.57	33.07	30.47	26.57	33.07	30.47	26.57	33.07	34.41	26.57	33.07	34.41	26.57	33.07	34.41	26.57	33.07	34.41
	Body_Height(H)	mm	235	205	210	235	245	249	235	287	249	235	287	249	235	287	300	235	287	300	235	287	300	235	287	300
		inch	9.25	8.07	8.27	9.25	9.65	9.80	9.25	11.30	9.80	9.25	11.30	9.80	9.25	11.30	11.81	9.25	11.30	11.81	9.25	11.30	11.81	9.25	11.30	11.81
Packing(W*D*H)	Packing_Length(W)	mm	1145	955	1070	1360	900	1305	1725	955	1305	1725	955	1305	1725	900	1405	1725	900	1405	1725	900	1405	1725	900	1405
		inch	45.08	37.60	42.13	53.54	35.43	51.38	67.91	37.60	51.38	67.91	37.60	51.38	67.91	35.43	55.31	67.91	35.43	55.31	67.91	35.43	55.31	67.91	35.43	55.31
	Packing_Width(D)	mm	755	955	725	755	900	805	755	955	805	755	955	805	755	900	915	755	900	915	755	900	915	755	900	915
		inch	29.72	37.60	28.54	29.72	35.43	31.69	29.72	37.60	31.69	29.72	37.60	31.69	29.72	35.43	36.02	29.72	35.43	36.02	29.72	35.43	36.02	29.72	35.43	36.02
	Packing_Height(H)	mm	318	217	280	318	265	315	318	307	315	318	307	315	318	307	365	318	307	365	313	307	365	313	307	365
		inch	12.32	8.54	10.63	12.32	10.12	12.01	12.32	11.50	12.01	12.32	11.50	12.01	12.32	11.50	13.98	12.32	11.50	13.98	12.32	11.50	13.98	12.32	11.50	13.98
Net/Gross weight	Net weight	Kg	27.4	23	24	30.3	25.6	32.6	40.9	30.3	34	40.9	30.3	34	41.2	30.1	47.8	41.2	30.1	47.8	45.5	30.4	47.7	45.5	30.4	47.7
		lb	60.41	50.71	52.91	66.80	56.44	71.87	90.17	66.80	74.96	90.17	66.80	74.96	90.83	66.36	105.38	90.83	66.36	105.38	100.31	67.02	105.16	100.31	67.02	105.16
	Gross weight	Kg	32.3	26.4	29.8	36	29.4	40	47.6	34	41.3	47.6	34	41.3	48	34	56.8	48	34	56.8	51.5	35.3	56.6	51.5	35.3	56.6
		lb	71.21	58.20	65.70	79.37	64.82	88.18	104.94	74.96	91.05	104.94	74.96	91.05	105.82	74.96	125.22	105.82	74.96	125.22	113.54	77.82	124.78	113.54	77.82	124.78
	Indoor side air flow(Hi)	m3/h	1250	914	901	1802.1	1488	1790	2432	1901	1718	2432	1901	1718	2415	1891	2691	2415	1891	2691	2621	1800	2777	2621	1800	2777
		CFM(ft3/min)	735.29	537.65	530.00	1060.06	875.29	1052.94	1430.59	1118.24	1010.59	1430.59	1118.24	1010.59	1420.59	1112.35	1582.94	1420.59	1112.35	1582.94	1541.76	1058.82	1633.53	1541.76	1058.82	1633.53
	Indoor side air flow(Mi)	m3/h	985	777	771	1560.9	1194	1537	2034	1430	1218	2034	1430	1218	2037	1426	2310	2037	1426	2310	2366	1600	2351	2366	1600	2351
		CFM(ft3/min)	579.41	457.06	453.53	918.18	702.35	904.12	1196.47	841.18	716.47	1196.47	841.18	716.47	1198.24	838.82	1358.82	1198.24	838.82	1358.82	1391.76	941.18	1382.94	1391.76	941.18	1382.94
	Indoor side air flow(Lo)	m3/h	784	640	666	1361.9	1086	1348	1755	1306	1029	1755	1306	1029	1763	1310	2021	1763	1310	2021	2223	1400	2005	2223	1400	2005
		CFM(ft3/min)	461.18	376.47	391.76	801.12	638.82	792.94	1032.35	768.24	605.29	1032.35	768.24	605.29	1037.06	770.59	1188.82	1037.06	770.59	1188.82	1307.65	823.53	1179.41	1307.65	823.53	1179.41
Drainage water pipe dia	Drainage water pipe dia	/	ODΦ25mm	ODΦ32mm	ODΦ25mm	ODΦ25mm	ODΦ32mm	ODΦ25mm	ODΦ25mm	ODΦ32mm	ODΦ25mm	ODΦ25mm	ODΦ32mm	ODΦ25mm	ODΦ25mm	ODΦ32mm	ODΦ25mm	ODΦ25mm	ODΦ32mm	ODΦ25mm	ODΦ25mm	ODΦ32mm	/	ODΦ25mm	ODΦ32mm	/
ESP	Rated	Pa	/	/	25	/	/	25	/	/	37	/	/	37	/	/	50	/	/	50	/	/	50	/	/	50
		/	/	/	0.10	/	/	0.10	/	/	0.15	/	/	0.15	/	/	0.20	/	/	0.20	/	/	0.20	/	/	0.20
	Range	Pa	/	/	0-100	/	/	0-160	/	/	0-160	/	/	0-160	/	/	0-160	/	/	0-160	/	/	0-160	/	/	0-160
Condenser																										
Market Model			MFM-F182C/HN1	MFM-F182C/HN1	MFM-F182C/HN1	MFM-F242C/HN1	MFM-F242C/HN1	MFM-F242C/HN1	MFM-F362C/HN1	MFM-F362C/HN1	MFM-F362C/HN1	MFM-F363C/HN1	MFM-F363C/HN1	MFM-F363C/HN1	MFM-F482C/HN1	MFM-F482C/HN1	MFM-F482C/HN1	MFM-F483C/HN1	MFM-F483C/HN1	MFM-F483C/HN1	MFM-F602C/HN1	MFM-F602C/HN1	MFM-F602C/HN1	MFM-F603C/HN1	MFM-F603C/HN1	MFM-F603C/HN1
			MOCA30U-18CN1-NB	MOCA30U-18CN1-NB	MOCA30U-18CN1-NB	MOCA30U-24CN1-NB	MOCA30U-24CN1-NB	MOCA30U-24CN1-NB	MOD30U-36CN1-NB8	MOD30U-36CN1-NB8	MOD30U-36CN1-NB8	MOD30U-36CN1-DB8	MOD30U-36CN1-DB8	MOD30U-36CN1-DB8	MODU-48CN1-NB8	MODU-48CN1-NB8	MODU-48CN1-NB8	MODU-48CN1-DB8	MODU-48CN1-DB8	MODU-48CN1-DB8	MOE30U-60CN1-NB8	MOE30U-60CN1-NB8	MOE30U-60CN1-NB8	MOE30U-60CN1-DB8	MOE30U-60CN1-DB8	MOE30U-60CN1-DB8
Power supply	Voltage type	/	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220V,3Ph	220V,3Ph	220V,3Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220V,3Ph	220V,3Ph	220V,3Ph	220-230V,1Ph	220-230V,1Ph	220-230V,1Ph	220V,3Ph	220V,3Ph	220V,3Ph
	Supply frequency	/	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz
Max.Input consumption	Max.Input consumption	W	2500	2500	2500	3500	3500	3500	5000	5000	5000	5490	5490	5490	6250	6250	6250	6900	6900	6900	7150	7150	7150	7150	7150	7150
Max.Current	Max.Current	A	11.5	11.5	11.5	16	16	16	24	24	24	17.3	17.3	17.3	30.5	30.5	30.5	22	22	22	36.0	36.0	36.0	20.5	20.5	20.5
Compressor	Model	/	PA170M2A-3FT6	PA170M2A-3FT6	PA170M2A-3FT6	PA241G2C-3MT3	PA241G2C-3MT3	PA241G2C-3MT3	LN32NQAMC	LN32NQAMC	LN32NQAMC	ATH356UG3C9EU	ATH356UG3C9EU	ATH356UG3C9EU	ZP49KUE-PFV-502	ZP49KUE-PFV-502	ZP49KUE-PFV-502	ZP49KUE-TF5-52E	ZP49KUE-TF5-52E	ZP49KUE-TF5-52E	ZP57KSE-PFV-522	ZP57KSE-PFV-522	ZP57KSE-PFV-522	ZP57KSE-TF5-522	ZP57KSE-TF5-522	ZP57KSE-TF5-522
	Type	/	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL
	Brand	/	GMCC	GMCC	GMCC	GMCC	GMCC	GMCC	MITSUBISHI	MITSUBISHI	MITSUBISHI	HITACHI	HITACHI	HITACHI	EMERSON	EMERSON	EMERSON	EMERSON	EMERSON	EMERSON	EMERSON	EMERSON	EMERSON	COPELAND	COPELAND	COPELAND
	Capacity	W	5055/5155	5055/5155	5055/5155	7215/7300	7215/7300	7215/7300	10120/10150	10120/10150	10120/10150	10350	10350	10350	14300	14300	14300	14400	14400	14400	16800	16800	16800	16900	16900	16900
	Input	W	1645/1660	1645/1660	1645/1660	2310/2315	2310/2315	2310/2315	3260/3310	3260/3310	3260/3310	3400	3400	3400	4540	4540	4540	4580	4580	4580	5460	5460	5460	5320	5320	5320
	Rated current	A	8.05/7.35	8.05/7.35	8.05/7.35	11.15/10.25	11.15/10.25	11.15/10.25	15.6/15.5	15.6/15.5	15.6/15.5	10.9	10.9	10.9	25.1	25.1	25.1	18.7	18.7	18.7	25.6	25.6	25.6	15.2	15.2	15.2
	LRA (Locked rotor amp)	A	41.9	41.9	41.9	62	62	62	72/86	72/86	72/86	81	81	81	138.0	138.0	138.0	136.8	136.8	136.8	178.0	178.0	178.0	136	136	136
	Thermal protector	/	UP3-64	UP3-64	UP3-64	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/
	Thermal protector position	/	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL	INTERNAL
	Capacitor	μF	40.0	40.0	40.0	60.0	60.0	60.0	45.0	45.0	45.0	0.0	0.0	0.0	80.0	80.0	80.0	0.0	0.0	0.0	80.0	80.0	80.0	0.0	0.0	0.0
	Refrigerant oil/oil charge	mL	VG74/420	VG74/420	VG74/420	ESTER OIL VG74/700	ESTER OIL VG74/700	ESTER OIL VG74/700	FV50S/750	FV50S/750	FV50S/750	A68HES-H OR EQUIV	A68HES-H OR EQUIV	A68HES-H OR EQUIV	3MAF POE/1242	3MAF POE/1242	3MAF POE/1242	3MAF POE/1242	3MAF POE/1242	3MAF POE/1242	3MAF POE/1242	3MAF POE/1242	3MAF POE/1242	3MAF POE/1242	3MAF POE/1242	3MAF POE/1242
Outdoor Fan motor	Model	/	YKT-63-6-200L	YKT-63-6-200L	YKT-63-6-200L	YKT-63-6-200L	YKT-63-6-200L	YKT-63-6-200L	YKS-190-8-3	YKS-190-8-3	YKS-190-8-3	YKS-190-8-3	YKS-190-8-3	YKS-190-8-3	YKT-65-6-41	YKT-65-6-41	YKT-65-6-41	YKT-65-6-41	YKT-65-6-41	YKT-65-6-41	YKT-90-6-9	YKT-90-6-9	YKT-90-6-9	YKT-90-6-9	YKT-90-6-9	YKT-90-6-9
	Input	W	136.0	136.0	136.0	136.0	136.0	136.0	270.0	270.0	270.0	270.0	270.0	270.0	164.0	164.0	164.0	164.0	164.0	164.0	143.0	143.0	143.0	143.0	143.0	143.0
	RLA (Rated current)	A	0.6	0.6	0.6	0.6	0.6	0.6	1.1	1.1	1.1	1.1	1.1	1.1	0.68	0.68	0.68	0.72	0.72	0.72	0.65	0.65	0.65	0.65	0.65	0.65
	LRA (Locked rotor amp)	A	/	/	/	0.9	0.9	0.9	/	/	/	2.4	2.4	2.4	0.86	0.86	0.86	0.945	0.945	0.945	0.76	0.76	0.76	0.76	0.76	0.76
	Winding resistance	Ω	/	/	/	131	131	131	/	/	/	32.5	32.5	32.5	38	38	38	56.2	56.2	56.2	74	74	74	74	74	74
	Speed(High/Mi/Low)	r/min	930/830	930/830	930/830	930/830	930/830	930/830	830/780	830/780	830/780	830/780	830/780	830/780	815	815	815	815	815	815	860/780	860/780	860/780	860/780	860/780	860/780
	Capacitor	μF	3	3	3	3	3	3	10	10	10	6	6	6	3.5UF/450V	3.5UF/450V	3.5UF/450V	3.5	3.5	3.5	5	5	5	5	5	5
	Capacitor class	/	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2	P2
	Insulation class	/	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
Condenser	Number of rows	/	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
	Tube outside dia	mm	Φ5	Φ5	Φ5	Φ5	Φ5	Φ5	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7	Φ7
	Tube outside type	/	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube
	Tube pitch(a)x row pitch(b)	mm	19.5x11.6	19.5x11.6	19.5x11.6	19.5x11.6	19.5x11.6	19.5x11.6	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37	21x13.37
	Fin spacing	mm	1.2	1.2	1.2	1.2	1.2	1.2	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4
	Fin type (code)	/	Unhydrophilic aluminiu	Unhydrophilic aluminiu	Unhydrophilic aluminiu	Unhydrophilic aluminiu	Unhydrophilic aluminiu	Unhydrophilic aluminiu	Unhydrophilic aluminiu	Unhydrophilic aluminiu	Unhydrophilic aluminiu	Unhydrophilic aluminiu	Unhydrophilic aluminiu	Unhydrophilic aluminiu	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum
	Coil length x height x width	mm	768x663x23.2	768x663x23.2	768x663x23.2	768x663x23.2	768x663x23.2	768x663x23.2	1005x756x26.74	1005x756x26.74	1005x756x26.74	1005x756x26.74	1005x756x26.74	1005x756x26.74	850x1113x40.11	850x1113x40.11	850x1113x40.11	850x1113x40.11	850x1113x40.11	850x1113x40.11	985x1260x40.11	985x1260x40.11	985x1260x40.11	985x1260x40.11	985x1260x40.11	985x1260x40.11
	Number of circuits	/	4	4	4	4	4	4	6	6	6	6	6	6	8	8	8	8	8	8	14	14	14	14	14	14
Outdoor side air flow(Hi)	Outdoor side air flow(Hi)	m3/h	2800	2800	2800	2800	2800	2800	5100	5100	5100	5100	5100	5100	6500	6500	6500	6500	6500	6500	7200	7200	7200	7200	7200	7200
		CFM(ft3/min)	1647.06	1647.06	1647.06	1647.06	1647.06	1647.06	3000.00	3000.00	3000.00	3000.00	3000.00	3000.00	3823.53	3823.53	3823.53	3823.53	3823.53	3823.53	4235.29	4235.29	4235.29	4235.29	4235.29	4235.29
Dimension(W*D*H)	Body_Length(W)	mm	845	845	845	845	845	845	946	946	946	946	946	946	900	900	900	900	900	900	952	952	952	952	952	952
		inch	33.27	33.27	33.27	33.27	33.27	33.27	37.24	37.24	37.24	37.24	37.24	37.24	35.43	35.43	35.43	35.43	35.43	35.43	37.48	37.48	37.48	37.48	37.48	37.48
	Body_Width(D)	mm	363	363	363	363	363	363	410	410	410	410	410	410	350	350	350	350	350	350	415	415	415	415	415	415
		inch	14.29	14.29	14.29	14.29	14.29	14.29	16.14	16.14	16.14	16.14	16.14	16.14	13.78	13.78	13.78	13.78	13.78	13.78	16.34	16.34	16.34	16.34	16.34	16.34
	Body_Height(H)	mm	702	702	702	702	702	702	810	810	810	810	810	810	1170	1170	1170	1170	1170	1170	1333	1333	1333	1333	1333	1333
		inch	27.64	27.64	27.64	27.64	27.64	27.64	31.89	31.89	31.89	31.89	31.89	31.89	46.06	46.06	46.06	46.06	46.06	46.06	52.48	52.48	52.48	52.48	52.48	52.48
Packing(W*D*H)	Packing_Length(W)	mm	965	965	965	965	965	965	1090	1090	1090	1090	1090	1090	1032	1032	1032	1032	1032	1032	1095	1095	1095	1095	1095	1095
		inch	37.99	37.99	37.99	37.99	37.99	37.99	42.91	42.91	42.91	42.91	42.91	42.91	40.63	40.63	40.63	40.63	40.63	40.63	43.11	43.11	43.11	43.11	43.11	43.11
	Packing_Width(D)	mm	395	395	395	395	395	395	500	500	500	500	500	500	443	443	443	443	443	443	495	495	495	495	495	495
		inch	15.55	15.55	15.55	15.55	15.55	15.55	19.69	19.69	19.69	19.69	19.69	19.69	17.44	17.44	17.44	17.44	17.44	17.44	19.49	19.49	19.49	19.49	19.49	19.49
	Packing_Height(H)	mm	775	775	775	775	775	775	885	885	885	885	885	885	1307	1307	1307	1307	1307	1307	1480	1480	1480	1480	1480	1480
		inch	30.12	30.12	30.12	30.12	30.12	30.12	34.45	34.45	34.45	34.45	34.45	34.45	51.46	51.46	51.46	51.46	51.46	51.46	58.27	58.27	58.27	58.27	58.27	58.27
Net/Gross weight	Net weight	Kg	42.2	42.2	42.2	47.9	47.9	47.9	67.2	67.2	67.2	66.1	66.1	66.1	90.1	90.1	90.1	87.5	87.5	87.5	110.4	110.4	110.4	109.1	109.1	109.1
		lb	93.03	93.03	93.03	105.60	105.60	105.60	148.15	148.15	148.15	145.72	145.72	145.72	198.63	198.63	198.63	192.90	192.90	192.90	243.39	243.39	243.39	240.52	240.52	240.52
	Gross weight	Kg	45.4	45.4	45.4	51.4	51.4	51.4	73	73	73	70.6	70.6	70.6	101.7	101.7	101.7	99.0	99.0	99.0	123	123	123	121.6	121.6	121.6
		lb	100.09	100.09	100.09	113.32	113.32	113.32	160.94	160.94	160.94	155.64	155.64	155.64	224.21	224.21	224.21	218.26	218.26	218.26	271.17	271.17	271.17	268.08	268.08	268.08
Refrigerant	Refrigerant type	/	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
	Refrigerant charge	/	1.2	1.2	1.2	1.35	1.35	1.35	2.5	2.5	2.5	2.5	2.5	2.5	3.4	3.4	3.4	3.4	3.4	3.4	4.1	4.1	4.1	4.1	4.1	4.1
	Refrigerant charge unit	/	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg
	Additional refrigerant per metre	g/m	/	/	/	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65	65
		oz/ft	/	/	/	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69
	Loading quantity _40'HQ (ESTIMATED)	set	125	143	118	103	107	128	138	138	138	138	138	138	108	108	108	108	108	108	48	48	48	48	48	48