



CASSETTE 60HZ R-32 INVERTER MEXICO
YKK(J)F12-55BZTMCMORX

Indoor Unit

- Auto Restart
- 360° Air outlet
- Low noise
- Super slim design
- Build-in Drain pump
- Washable air filter
- Follow me function
- Fresh air intake
- Easy clean design
- Wired controller (Optional)

Remote Control

- 5 operation modes: Auto, Cool, Dry, Heat, Fan only
- Multi-speed fan setting: High/Medium/Low/Auto
- 24-hour timer setting
- Turbo cool setting
- Background light LCD display
- Real-time clock display

Condensing Unit

- Compact size
- More sturdy and durable
- High efficiency compressor
- Low noise
- 3-minute protection
- Valve protection
- Easier installation
- Easier maintenance
- Universal design



12K



18K



24K



36K&48K&60K



CO



HP



The YORK® line of cassette Air conditioners includes a wide range of sizes to give you more flexibility in your product offering. Each model is designed to provide comfort and efficiency, in an easy-to-operate unit and the sleek design fits a variety of spaces, whether it's in a home or office. Models meet the highest energy efficiency ratings, so less energy is consumed without sacrificing comfort and performance. Both the condensing and indoor units are engineered for quiet operation. And comfort control settings are easily changed with the touch of a button on the remote control.

Features and benefits



Self Diagnosis

Clearly displayed failure codes allow for quicker troubleshooting and easier maintenance.



24-Hour Timer

Allows programmed start times up to 24 hours in advance for flexible and more convenient operation.



3-Minute Protection

A 3-minute delay before the compressor will restart helps avoid compressor damage and work time.



Auto Restart

Unit is automatically returned to previous operating conditions after a power outage, for simplified operation.



Built-in Drain Pump

Built-in drain pump can pump condensation to a high level, which facilitates draining condensation from indoor unit and makes installation easier.



Washable Filter

Washable filter allows for convenient service and maintenance.



Multi-Speed Fan

Multi-speed fan helps satisfy various airflow requirements.



Low Ambient Cooling at -15°C

The AC will run in cooling mode when outdoor temperature is below -15°C to meet special user-requested applications.



DC Inverter Compressor

DC inverter compressor provides more comfortable indoor environment, higher performance in partial load and better heating performance in low ambient temperature than fixed compressor.



R-32

Environmentally-friendly refrigerant cools and heats more efficiently without destroying the ozone layer.



Inner Groove Copper Tube

Inner groove copper tubing allows more refrigerant to pass through, improving heat exchange by 30 to 50% when compared to traditional copper tubing, and lowering power consumption while keeping output capacity at the same level.

Specification

YORK Set model			YKFF12BZTMC MORX	YKFF18BZTMC MORX	YKFF24BZTMC MORX	YKFF36BZTMC MORX
YORK Indoor model			YKFF12BXTMCM-RX	YKFF18BXTMCM-RX	YKFF24BXTMCM-RX	YKFF36BXTMCM-RX
YORK Outdoor model			YUKF12BYTMC MO-X	YUKF18BYTMC MO-X	YUKF24BYTMC MO-X	YUKF36BYTMC MO-X
Power supply (Indoor)		V- Ph-Hz	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ
Power supply (Outdoor)		V- Ph-Hz	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ
Cooling (Standard conditions)	Capacity	Btu/h	12000	18000	24000	36000
	range		(4200-13440)	(6300-20160)	(8400-26880)	(12600-40320)
	Input	W	1015	1550	2320	4250
	range		(355.25-1136.8)	(542.5-1736)	(1029.0-2592.0)	(1891.25-5325.0)
	Current	A	4.5	6.9	10.2	18.5
	range		(1.575-5.04)	(2.415-7.728)	(3.57-11.42)	(6.51-20.72)
	EER	W/W	3.47	3.40	3.03	2.48
	SEER(AHRI)		21.5	19.0	19.0	16.0
Heating (Standard conditions)	Capacity	Btu/h	13000	19000	26000	36000
	range		(4550-14560)	(6650-21280)	(9100-29120)	(12600-40320)
	Input	W	1020	1560	1900	3050
	range		(357-1142.4)	(546-1747.2)	(665.00-2120.00)	(1067.50-3408.00)
	Current	A	4.5	6.8	8.5	13.5
	range		(1.575-5.04)	(2.38-7.616)	(2.98-9.52)	(4.73-15.12)
	COP	W/W	3.74	3.57	4.01	3.46
	MAX Power Input	W	1850	2950	3700	4700
MAX Current		A	9	13.5	19	21.5
Indoor fan motor	type		DC	DC	DC	AC
	Qty		1	1	1	1
	Input	W	/	/	/	/
	Capacitor	μF	/	/	/	4
	Speed(Hi/Mi/Lo)	r/min	800/750/700	800/750/700	608/552/496	630/500/420
Indoor air flow (Hi/Mi/Lo)		m ³ /h	620/520/330	660/540/300	1247/1118/992	1750/1400/1150
Indoor noise level (Hi/Mi/Lo)		dB(A)	42/38.5/31.5	44/41/31.5	45/42.5/37	52.5/46.5/42
Indoor unit	Dimension(WxDxH)(body)	mm	570x570x245	570x570x245	830x830x205	830x830x245
	Dimension (WxDxH)(panel)	mm	620x620x50	620x620x50	950x950x55	950x950x55
	Packing (WxDxH)(body)	mm	715x640x295	715x640x295	910x910x250	910x910x290
	Packing (WxDxH)(panel)	mm	715x700x115	715x700x115	1035x1035x90	1035x1035x90
	Net/Gross weight(body)	kg	16.1/18.8	16.2/19	21.6/25.4	25.5/30.3
	Net/Gross weight(panel)	kg	2.7/4.3	2.7/4.3	6/9	6/9
Qty' per 20' /40' /40'HQ		Indoor unit	216/432/486	216/432/486	108/234/260	96/208/234
Compressor	Type		ROTARY	ROTARY	ROTARY	ROTARY
	Capacity	W	1930/3100 ±3%	4385	4780/7600	4780/7600
	Input	W	292/765 ±3%	1140	805/2045	805/2045
	Rated current(RLA)	A	2.15/4.65 ±3%	7.50	4.15/9.30	4.15/9.30
	Refrigerant oil/oil charge	ml	ESTER OIL VG74 300±10	VG74 440	VG74 620	VG74 620
Outdoor fan motor	type		DC	DC	DC	DC
	Speed	r/min	780/600	760/650	830/550	900/700/600
Outdoor noise level		dB(A)	57	58	60	63
Throttle type		/	EXV	EXV	EXV+Throttle valve	EXV+Throttle valve
Outdoor unit	Dimension(W*D*H)	mm	765x303x555	805x330x554	890x342x673	890x342x673
	Packing (W*D*H)	mm	887x337x610	915x370x615	995x398x740	995x398x740
	Net/Gross weight	kg	26.6/29	32.5/35.2	41.9/45.2	47.6/51.1
Refrigerant type		kg	R32/0.71	R32/1.15	R32/1.4	R32/1.9
Design pressure		MPa	4.3/1.7	4.3/1.7	4.3/1.7	4.3/1.7
Refrigerant piping	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/12.7mm(1/2in)	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/15.9mm(5/8in)
	Max. refrigerant pipe length	m	25	30	50	50
	Max. difference in level	m	10	20	25	25
Operation temperature		°C	17~30	17~30	17~30	17~30
Room temperature	Indoor(cooling/ heating)	°C	16 ~ 32/0 ~ 30	16 ~ 32/0 ~ 30	16 ~ 32/0 ~ 30	17 ~ 32/0 ~ 30
	Outdoor(cooling/heating)	°C	-15 ~ 50/-20 ~ 24	-15 ~ 50/-20 ~ 24	-15 ~ 50/-20 ~ 24	0 ~ 50/-15 ~ 24
Qty' per 20' /40' /40'HQ		Outdoor unit	132/264/352	114/234/312	99/198/198	99/198/198

CASSETTE 60HZ R-32 INVERTER MEXICO

Specification

YORK Set model		YKXF48BZTMCMORX	YKXF55BZTMCMORX	YKJF12BZTMCMORX	YKJF18BZTMCMORX
YORK Indoor model		YKXF48BXTMCM-RX	YKXF55BXTMCM-RX	YKJF12BXTMCM-RX	YKJF18BXTMCM-RX
YORK Outdoor model		YUKF48BYTMCMO-X	YUKF55BYTMCMO-X	YUJF12BYTMCMO-X	YUJF18BYTMCMO-X
Power supply (Indoor)		V- Ph-Hz	220~230V_1Ph_60HZ	220~230V_1Ph_60HZ	220~230V_1Ph_60HZ
Power supply (Outdoor)		V- Ph-Hz	220~230V_1Ph_60HZ	220~230V_1Ph_60HZ	220~230V_1Ph_60HZ
Cooling (Standard conditions)	Capacity	Btu/h	48000	53000	12000
	range		(16800~53760)	(18550~59040)	(4200~13440)
	Input	W	5517	6100	1015
	range		(1931~6179)	(2714.5~6832.0)	(355.25~1136.8)
	Current	A	24	27	4.5
	range		(8.4~26.88)	(9.45~30.24)	(1.575~5.04)
	EER	W/W	2.55	2.55	3.47
Heating (Standard conditions)	SEER(AHRI)		16.0	15.5	21.5
	Capacity	Btu/h	58000	58000	/
	range		(20300~65040)	(20300~65040)	/
	Input	W	6450	6450	/
	range		(2257.50~7200.00)	(2257.50~7200.00)	/
	Current	A	28.5	28.5	/
	range		(9.98~31.92)	(9.98~31.92)	/
MAX Power Input		W/W	2.64	2.64	/
MAX Current		W	7300	7300	1850
Indoor fan motor	type	A	32	32	9
	Qty		1	1	1
	Input	W	/	/	/
	Capacitor	μF	4	4	/
	Speed(Hi/Mi/Lo)	r/min	670/580/490	670/580/490	800/750/700
Indoor air flow (Hi/Mi/Lo)		m ³ /h	1850/1550/1350	1850/1550/1350	620/520/330
Indoor noise level (Hi/Mi/Lo)		dB(A)	////	////	42/38.5/31.5
Indoor unit	Dimension(WxDxH)(body)	mm	830x830x245	830x830x245	570x570x245
	Dimension(WxDxH)(panel)	mm	950x950x55	950x950x55	620x620x50
	Packing (WxDxH)(body)	mm	910x910x290	910x910x290	715x640x295
	Packing (WxDxH)(panel)	mm	1035x1035x90	1035x1035x90	715x700x115
	Net/Gross weight(body)	kg	27.8/32.6	27.8/32.6	16.1/18.8
	Net/Gross weight(panel)	kg	6/9	6/9	2.7/4.3
Qty' per 20' /40' /40'HQ		Indoor unit	96/208/234	96/208/234	216/432/486
Compressor	Type		ROTARY	ROTARY	ROTARY
	Capacity	W	13700	13700	1930/3100 ± 3%
	Input	W	3700	3700	292/765 ± 3%
	Rated current(RLA)	A	7.02	7.02	2.15/4.65 ± 3%
	Refrigerant oil/oil charge	ml	VG74/1400	VG74/1400	ESTER OIL VG74 300±10
Outdoor fan motor	type		DC	DC	DC
	Speed	r/min	850/700/550	850/700/550	780/600
Outdoor noise level		dB(A)	/	/	57
Throttle type		/	EXV+Throttle valve	EXV+Throttle valve	EXV
Outdoor unit	Dimension(W*D*H)	mm	980x415x975	980x415x975	765x303x555
	Packing (W*D*H)	mm	1145x500x1080	1145x500x1080	887x337x610
	Net/Gross weight	kg	85.8/100	85.8/100	26.6/29
Refrigerant type		kg	R32/3	R32/3	R32/0.71
Design pressure		MPa	4.3/1.7	4.3/1.7	4.3/1.7
Refrigerant piping	Liquid side/ Gas side	mm(inch)	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/15.9mm(5/8in)	6.35mm(1/4in)/9.52mm(3/8in)
	Max. refrigerant pipe length	m	75	75	25
	Max. difference in level	m	30	30	10
Operation temperature		°C	17~30	17~30	17~30
Room temperature	Indoor(cooling/ heating)	°C	17 ~ 32/0 ~ 30	17 ~ 32/0 ~ 30	16 ~ 32/0 ~ 30
	Outdoor(cooling/heating)	°C	0 ~ 50/-15 ~ 24	0 ~ 50/-15 ~ 24	-15 ~ 50/-20 ~ 24
Qty' per 20' /40' /40'HQ		Outdoor unit	44/96/96	44/96/96	132/264/352

Specification

YORK Set model			YKJF24BZTMC MORX	YKJF36BZTMC MORX	YKJF48BZTMC MORX	YKJF55BZTMC MORX
YORK Indoor model			YKJF24BXTMCM-RX	YKJF36BXTMCM-RX	YKJF48BXTMCM-RX	YKJF55BXTMCM-RX
YORK Outdoor model			YUJF24BYTMC MO-X	YUJF36BYTMC MO-X	YUJF48BYTMC MO-X	YUJF55BYTMC MO-X
Power supply (Indoor)		V- Ph-Hz	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ
Power supply (Outdoor)		V- Ph-Hz	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ	220-230V_1Ph_60HZ
Cooling (Standard conditions)	Capacity	Btu/h	24000	36000	48000	53000
	range		(8400-26880)	(12600-40320)	(16800-53760)	(18550-59040)
	Input	W	2320	4250	5517	6100
	range		(1029.0-2592.0)	(1891.25-5325.0)	(1931-6179)	(2714.5-6832.0)
	Current	A	10.2	18.5	24	27
	range		(3.57-11.42)	(6.51-20.72)	(8.4-26.88)	(9.45-30.24)
	EER	W/W	3.03	2.48	2.55	2.55
SEER(AHRI)			19.0	16.0	16.0	15.5
Heating (Standard conditions)	Capacity	Btu/h	/	/	/	/
	range		/	/	/	/
	Input	W	/	/	/	/
	range		/	/	/	/
	Current	A	/	/	/	/
	range		/	/	/	/
	COP	W/W	/	/	/	/
MAX Power Input		W	3700	4700	7300	7300
MAX Current		A	19	21.5	32	32
Indoor fan motor	type		DC	AC	AC	AC
	Qty		1	1	1	1
	Input	W	/	/	/	/
	Capacitor	µF	/	4	4	4
	Speed(Hi/Mi/Lo)	r/min	608/552/496	630/500/420	670/580/490	670/580/490
Indoor air flow (Hi/Mi/Lo)		m³/h	1247/1118/992	1750/1400/1150	1850/1550/1350	1850/1550/1350
Indoor noise level (Hi/Mi/Lo)		dB(A)	45/42.5/37	52.5/46.5/42		
Indoor unit	Dimension(WxDxH)(body)	mm	830x830x205	830x830x245	830x830x245	830x830x245
	Dimension (WxDxH)(panel)	mm	950x950x55	950x950x55	950x950x55	950x950x55
	Packing (WxDxH)(body)	mm	910x910x250	910x910x290	910x910x290	910x910x290
	Packing (WxDxH)(panel)	mm	1035x1035x90	1035x1035x90	1035x1035x90	1035x1035x90
	Net/Gross weight(body)	kg	21.6/25.4	25.5/30.3	27.8/32.6	27.8/32.6
	Net/Gross weight(panel)	kg	6/9	6/9	6/9	6/9
Qty` per 20` /40` /40'HQ		Indoor unit	108/234/260	96/208/234	96/208/234	96/208/234
Compressor	Type		ROTARY	ROTARY	ROTARY	ROTARY
	Capacity	W	4780/7600	4780/7600	13700	13700
	Input	W	805/2045	805/2045	3700	3700
	Rated current(RLA)	A	4.15/9.30	4.15/9.30	7.02	7.02
	Refrigerant oil/oil charge	ml	VG74 620	VG74 620	VG74/1400	VG74/1400
Outdoor fan motor	type		DC	DC	DC	DC
	Speed	r/min	830/550	900/700/600	850/700/550	850/700/550
Outdoor noise level		dB(A)	60	63	/	/
Throttle type		/	EXV+Throttle valve	EXV+Throttle valve	EXV+Throttle valve	EXV+Throttle valve
Outdoor unit	Dimension(W*D*H)	mm	890x342x673	890x342x673	980x415x975	980x415x975
	Packing (W*D*H)	mm	995x398x740	995x398x740	1145x500x1080	1145x500x1080
	Net/Gross weight	kg	41.9/45.2	47.6/51.1	85.8/100	85.8/100
Refrigerant type		kg	R32/1.4	R32/1.9	R32/3	R32/3
Design pressure		MPa	4.3/1.7	4.3/1.7	4.3/1.7	4.3/1.7
Refrigerant piping	Liquid side/ Gas side	mm(inch)	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/15.9mm(5/8in)
	Max. refrigerant pipe length	m	50	50	75	75
	Max. difference in level	m	25	25	30	30
Operation temperature		°C	17~30	17~30	17~30	17~30
Room temperature	Indoor(cooling/ heating)	°C	16 ~ 32/0 ~ 30	17 ~ 32/0 ~ 30	17 ~ 32/0 ~ 30	17 ~ 32/0 ~ 30
	Outdoor(cooling/heating)	°C	-15 ~ 50/-20 ~ 24	0 ~ 50/-15 ~ 24	0 ~ 50/-15 ~ 24	0 ~ 50/-15 ~ 24
Qty` per 20` /40` /40'HQ		Outdoor unit	99/198/198	99/198/198	44/96/96	44/96/96



INSTALL CONFIDENCE

Johnson Controls, the Johnson Controls logo, YORK are registered trademarks of Johnson Controls, Inc in the United States of America and other countries. Other trademarks used herein may be trademarks or registered trademarks of other companies.

FOR MORE INFORMATION CONTACT JOHNSONCONTROLS.COM

© 2024 Johnson Controls, Inc, P.O. Box 423, Milwaukee, WI 53201, All rights reserved worldwide.

SKK(J)F12-55BZTMC MORX-240704